





| Model | Capacity (mAh) | C-rate (Conti. /Peak) | Dimension (L x W x T mm) | Configuration | Voltage (V) | Weight (g) |
|-----------------------|----------------|-----------------------|--------------------------|---------------|-------------|------------|
| PQ-3350XQ3-3S1P | 3350 | 35C/70C | 142 x 46 x 21 | 3S1P | 11.1V | 250 |
| PQ-3350XQ3-6S1P | 3350 | 35C/70C | 142 x 46 x 41 | 6S1P | 22.2V | 525 |
| PQ-4000LP2-3S1P | 4000 | 18C/30C | 140 x 44 x 22 | 3S1P | 11.1V | 277 |
| PQ-5050XQ3-3S1P(long) | 5050 | 35C/70C | 163 x 46 x 25 | 3S1P | 11.1V | 385 |
| PQ-5050XQ3-6S1P(long) | 5050 | 35C/70C | 163 x 46 x 51 | 6S1P | 22.2V | 750 |
| PQ-5050XF2-3S1P(long) | 5050 | 40C/80C | 163 x 46 x 26 | 3S1P | 11.1V | 385 |
| PQ-5050XF2-6S1P(long) | 5050 | 40C/80C | 163 x 46 x 52 | 6S1P | 22.2V | 750 |
| PQ-6250XQ2-3S1P | 6250 | 30C/60C | 163 x 46 x 26 | 3S1P | 11.1V | 402 |
| PQ-6250XQ2-6S1P | 6250 | 30C/60C | 163 x 46 x 52 | 6S1P | 22.2V | 800 |
| PQ-9000XP2-6S1P | 9000 | 25C/50C | 220 x 70 x 36 | 6S1P | 22.2V | 1280 |